



作業半径	最大作業半径		
	32.0m	35.0m	40.0m
0.0m	12.00t		
0.4m	↓	12.00t	
0.8m	↓	↓	9.00t
3.0m	↓	↓	↓
4.0m	↓	↓	↓
5.0m	↓	↓	9.00t
6.0m	↓	↓	7.85t
7.0m	↓	↓	7.04t
8.0m	↓	↓	6.42t
9.0m	↓	↓	5.95t
10.0m	↓	↓	5.57t
11.0m	↓	↓	5.26t
12.0m	↓	↓	5.00t
13.0m	↓	↓	4.78t
14.0m	↓	↓	4.59t
15.0m	↓	↓	4.42t
16.0m	↓	↓	4.27t
17.0m	↓	↓	4.15t
18.0m	↓	12.00t	4.04t
19.0m	↓	11.29t	3.94t
20.0m	12.00t	10.66t	3.85t
21.0m	11.37t	10.09t	3.77t
22.0m	10.79t	9.57t	3.70t
23.0m	10.26t	9.10t	3.64t
24.0m	9.78t	8.66t	3.58t
25.0m	9.33t	8.26t	3.52t
26.0m	8.91t	7.88t	3.47t
27.0m	8.53t	7.53t	3.42t
28.0m	8.19t	7.21t	3.38t
29.0m	7.88t	6.91t	3.34t
30.0m	7.58t	6.64t	3.30t
31.0m	7.29t	6.39t	3.27t
32.0m	7.00t	6.15t	3.23t
33.0m		5.93t	3.20t
34.0m		5.71t	3.17t
35.0m		5.50t	3.14t
36.0m			3.11t
37.0m			3.08t
38.0m			3.06t
39.0m			3.03t
40.0m			3.0t

名称		JCC-230 II		
定格荷重	t	12 - 7	12 - 5.5	9 - 3
作業半径	m	20 - 32	18 - 35	5 - 40
揚程	m	190		
速度	巻上	早巻	72 - 36/86 - 44 (0t - 6t)	
		遅巻	36 - 18/43 - 22 (0t - 12t)	
	起伏	sec	159/132	
	旋回	r.p.m	0.4/0.48	
電動機	巻上	kW	0.6/0.72	
			高速 30 低速 55	
	起伏	kW	25	
	旋回		8.5	
昇降	22			
操作		運転室		
電源容量	kVA · A	150 · 350		
電源	V	50/60Hz		
		200/220		

クライミングクレーン

ダム用クレーン

ジブクレーン

固定式ジブクレーン 外装取付用

解体用ジブクレーン

解体用小分解型ジブクレーン

クレーン周辺機器その他

参考資料