



作業半径	最大作業半径				
	20.0m	25.0m	30.0m	35.0m	40.0m
0.0m	2.7t	2.7t	2.7t	2.7t	2.7t
↓	↓	↓	↓	↓	↓
17.0m	↓	↓	↓	↓	2.7t
18.0m	↓	↓	↓	↓	2.5t
19.0m	↓	↓	↓	↓	2.3t
20.0m	2.7t	↓	↓	↓	2.2t
21.0m		↓	↓	↓	2.1t
22.0m		↓	↓	2.7t	2.0t
23.0m		↓	↓	2.6t	1.9t
24.0m		↓	↓	2.5t	1.8t
25.0m		2.7t	↓	2.4t	1.7t
26.0m			↓	2.2t	1.6t
27.0m			2.7t	2.1t	1.5t
28.0m			2.5t	2.0t	1.5t
29.0m			2.4t	2.0t	1.4t
30.0m			2.3t	1.9t	1.3t
31.0m				1.8t	1.3t
32.0m				1.7t	1.2t
33.0m				1.6t	1.2t
34.0m				1.6t	1.2t
35.0m				1.5t	1.1t
36.0m					1.1t
37.0m					1.0t
38.0m					1.0t
39.0m					1.0t
40.0m					1.0t

名称		JCL040H			
定格荷重	t	2.7	2.7 - 2.3	2.7 - 1.5	2.7 - 1
作業半径	m	25	26.7 - 30	22 - 35	17 - 40
揚程	m	130			
速度	巻上	高速	25 (0 - 2.7t)		
		中速	12.5 (0 - 2.7t)		
		低速	2.1 (0 - 2.7t)		
	起伏	sec	11/5.5 / 13.2/6.6		
	旋回	r.p.m	50/60Hz		
電動機	昇降	m/min	0.8/0.9		
	巻上		26		
	起伏		10/5		
	旋回		5.5		
	昇降		5.5		
操作		運転室、無線			
電源容量	KVA · A	80 · 400			
電源	V	50/60Hz			