



作業半径	最大作業半径				
	22.0m	27.0m	30.0m	35.0m	40.0m
0.0m	6.00t	6.00t	6.00t	6.00t	6.00t
1.0m	6.80t	7.70t	7.70t	7.70t	6.30t
2.0m	7.60t	9.30t	9.30t	9.30t	6.70t
3.0m	8.40t	11.00t	11.00t	11.00t	7.00t
4.0m	9.20t	↓	↓	↓	↓
5.0m	10.00t	↓	↓	↓	↓
↓	↓	↓	↓	↓	↓
18.0m	↓	↓	↓	11.00t	↓
19.0m	↓	↓	11.00t	10.40t	↓
20.0m	↓	11.00t	10.40t	9.80t	7.00t
21.0m	↓	10.30t	9.80t	9.30t	6.70t
22.0m	10.00t	9.60t	9.30t	8.80t	6.40t
23.0m		9.00t	8.80t	8.30t	6.10t
24.0m		8.50t	8.30t	7.80t	5.80t
25.0m		8.00t	7.80t	7.40t	5.50t
26.0m		7.60t	7.40t	7.00t	5.30t
27.0m		7.20t	7.00t	6.60t	5.00t
28.0m			6.70t	6.30t	4.80t
29.0m			6.30t	6.00t	4.60t
30.0m			6.00t	5.70t	4.40t
31.0m				5.40t	4.20t
32.0m				5.10t	4.00t
33.0m				4.90t	3.90t
34.0m				4.70t	3.70t
35.0m				4.50t	3.60t
36.0m					3.40t
37.0m					3.30t
38.0m					3.20t
39.0m					3.10t
40.0m					3.00t

名称		JCL180NK					
定格荷重	t	10	11 - 7.2	11 - 6	11 - 4.5	7 - 3	
作業半径	m	22	20 - 27	19 - 30	18 - 35	20 - 40	
揚程	m	178	168	163	156	110	
速度	巻上	m/min	33 - 100 (11 - 2t)				
	起伏	s	98	94	92	89	100
	旋回	r.p.m	0.5				
	昇降	m/min	0.3/0.36				
電動機	巻上	kW	75				
	起伏		15				
	旋回		7.5				
	昇降		11				
操作		運転室					
電源容量	kVA · A	150 · 400					
電源	V	50/60Hz					