



作業半径	最大作業半径			
	22m	25m	30m	35m
5m		12t	10t	
6m	12t	↓	↓	8.0t
7m	↓	↓	↓	↓
8m	↓	↓	↓	↓
9m	↓	↓	↓	↓
10m	↓	↓	↓	↓
11m	↓	↓	↓	↓
12m	↓	↓	↓	↓
13m	↓	↓	↓	↓
13.5m	↓	12t	10t	↓
14m	↓	11.4t	9.5t	↓
14.5m	12t	10.9t	9.1t	↓
15m	11.5t	10.5t	8.8t	8t
16m	10.6t	9.7t	8.2t	7.5t
17m	9.9t	9.1t	7.7t	7.1t
18m	9.3t	8.5t	7.3t	6.7t
19m	8.7t	8.0t	6.9t	6.3t
20m	8.2t	7.6t	6.6t	6t
21m	7.7t	7.2t	6.3t	5.6t
22m	7.3t	6.8t	6.0t	5.3t
23m		6.5t	5.7t	5t
24m		6.2t	5.4t	4.7t
25m		6t	5.1t	4.5t
26m			4.8t	4.2t
27m			4.6t	4t
28m			4.4t	3.8t
29m			4.2t	3.6t
30m			4t	3.4t
31m				3.2t
32m				3.1t
33m				2.9t
34m				2.8t
35m				2.7t

名称		OJ-150R 走行式			
定格荷重	t	12 - 7.3	12 - 6	10 - 4	8 - 2.7
作業半径	m	14.5 - 22	13.5 - 25	13.5 - 30	15 - 35
揚程	m	200			
速度	巻上 m/min	37.5 (12t) / 70 (6t) / 120 (3.1t)			
	起伏 sec	96			
	旋回 r.p.m	0.65			
	走行 m/min	8.8			
電動機	巻上	kW	90		
	起伏		22		
	旋回		5.5		
	走行		2.2 2台		
操作		運転室			
電源容量	kVA · A	200 · 300			
電源	V	50/60Hz			
		400/440			

クライミングクレーン

ダム用クレーン

ジブクレーン

固定式ジブクレーン 外装取付用

解体用ジブクレーン

解体用小分解型ジブクレーン

クレーン周辺機器その他

参考資料