



作業半径	最大作業半径		
	15.0m	20.0m	25.0m
0.0m	2.8t	2.8t	2.8t
5.0m	↓	↓	↓
6.0m	↓	↓	↓
7.0m	↓	↓	↓
8.0m	↓	↓	2.8t
9.0m	↓	↓	2.7t
10.0m	↓	↓	2.6t
11.0m	↓	↓	2.4t
12.0m	↓	↓	2.3t
13.0m	↓	↓	2.2t
14.0m	↓	↓	2.1t
15.0m	2.8t	↓	2.0t
16.0m		2.8t	1.8t
17.0m		2.6t	1.7t
18.0m		2.4t	1.6t
19.0m		2.1t	1.5t
20.0m		2.0t	1.5t
21.0m			1.4t
22.0m			1.3t
23.0m			1.3t
24.0m			1.2t
25.0m			1.2t

名称		OTS-45N		
定格荷重	t	2.8	2.8 - 2	2.8 - 1.2
作業半径	m	15	15.9 - 20	8.5 - 25
揚程	m	60 (最小半径時) / 49 (最大半径時)		
速度	巻上	m/min	21/2.5 / 25/3	
	起伏	sec	7.7/9.3	
	旋回	r.p.m	0.66/0.79	
	昇降	m/min	0.49/0.59	
電動機	巻上	kW	15/1.9	
	起伏		5.5	
	旋回		1.5	
	昇降		3.7	
操作		有線・無線		
電源容量	kVA・A	40・125		
電源	V	50/60Hz		